



Full access
high
density.

 **DEXION®**

Narrow aisle racking



*Minimise aisle.
Maximise space.*

Narrow aisle racking.

Your business:

You require greater storage density, your orders are complex and varied. Turnaround times are not critical, however you require immediate access to all products. Space in your facility is at a premium, so you're keen to get the most from what you've got.

Our solution:

Narrow aisle racking, as the name suggests, makes optimal use of floor area and roof height. Direct access to every pallet is achieved. The system is serviced by special forklift trucks. Operating cabins may be elevating or static.


The vital statistics:

Average locations used _____ 95%

Immediate accessibility _____ 100%

Stock rotation _____ Good

Average floor area by pallet position (sqm) _____ 0.45





Cherry picking.

← S14 → S11 →

Reduce Reuse Recycle Replace

Form with QR code and text.

← S11 → S10 →

Reduce Reuse Recycle Replace

Form with QR code and text.

Pick it
by hand.



Incorporate a range of
accessories.



The system is served by forklifts with elevating operator cabins. The operator hand picks.



Floor to ceiling optimisation.

Pick it
by pallet.



The forklift is guided within the operational aisles by wire guides. Therefore the risk of rack damage is minimised, resulting in lower maintenance.



The system is served by a turret or swing reach forklift. The mast of the fork head rotates either left or right as required. Forklifts often service multiple aisles.



Efficiency from A to B.

NO ENTRY TO TURRETS & STOCKPICKERS

EVEN

Broaden your narrow aisle system.



Mesh decks provide strength while allowing airflow and light filtration.



Chipboard retainers allow you to secure particleboard to beam levels.



Integrate a conveyor within existing racking structure for more efficient movement.

*Tested to the highest
international standards.*



Dexion
provides you
with more
component
choices.



Box beam. The market leader.



I-Beam. Don't pay for steel you don't need.



Open beam. For lighter loads.



Channel beam. Excellent load carrying capacity and resistance to damage.



Stepped beam. Designed for longspan shelf storage.



RHS beam. Excellent load carrying capacity and resistance to damage.



Spring-loaded automatic safety lock.



Galvanised standard baseplate.



Stiffened baseplate.



Heavy duty baseplate.



Narrow aisle baseplate.



90R upright.



90R galvanised upright.



90E upright.



100R upright.



100E upright.



Splice to connect uprights.



Dexion (Australia) Pty Limited. ABN 83 000 083 956. Head Office: 23 Tattersall Road, Kings Park NSW 2148. dexion.com.au
Dexion New Zealand. Incorp No. 1856839. Head Office: 423 East Tamaki Road, East Tamaki, Auckland 2013. dexion.co.nz

Whilst the utmost care is taken to ensure the accuracy of the information contained herein, it is provided in the understanding that the company shall under no circumstances be liable for any injuries, expenses or other losses which may in any way be attributable to the use or adoption of such data and/or design details. All dimensions indicated are nominal only. Dexion reserves the right to alter or amend without prior notice data and design details specified herein. Product specifications may vary between regions. Re-Order Code M061. F•S•A/DEX0031

